

WP QUADRA

3-layer Overall thickness 14 mm with 3,6 mm wear layer

INSTALLATION TECHNIQUES:

Dimensions: 1700 x 160 x 14 mm



Functionalities:



MAINTENANCE-FREE PARQUET: No maintenance required for ProActive+ surfaces in residential use.



HEALTHY PARQUET: Room climate control and allergy-friendly, antibacterial, breathable and antistatic properties.



SOUND-REDUCTION PARQUET: With full-surface bonding, excellent room sound insulation

Product description:

Production site:	Austria	Wood species/colors
Total thickness	3-layer construction 14 mm	Gratings/additional treatments:
Wear layer	3,6 mm solid wood	See current price list
Bottom layer material	Spruce with vertically arranged growth rings; header joint, made of high quality plywood	
Backing	Spruce	
Processing	4-sided tongue and groove, bevel on the longitudinal and header joints, optionally brushed	
Moisture content	long seasoned and technically dried wood (moisture content 7 % ± 1 %)	
Composition	Approx. 92% renewable raw material wood, 7% of combined water and approx. 1% synthetic material	
Under-floor heating	Oak ideally suited. Weitzer Parkett recommends complete adhesion	
Fire resistance	C _{fl} -s1 (hardly inflammable) for all factory-applied surfaces (please pay attention to the conditions for installation)	
Heat conductivity resistance	0,104 m ² K/W	
Renovation	multiple sanding possible	
Degree of hardness according to Brinell	23-42 N/mm ²	
Ecological Responsibility		



Surfaces:



PROACTIVE+ – THE NATURAL MATT SURFACE FINISH

Combines the advantages of the ProStrong surface finish with the appearance of the natural Oiled finish ProVital. Meets Class C of ONORM C 2354 (the highest standard for anti-scratch and resistance against certain chemicals etc.). Combines antistatic and antibacterial qualities. Meets the requirements of the chair-rollers test according to EN 425. The pendulum value according to ÖNORM EN 13036-4 is 90.



PROVITAL finish – THE NATURAL OILED SURFACE FINISH

Oil from natural, plant-based raw materials and natural resins, sealing the open pores. Extremely breathable. Local renovation is possible. Surface oiled at the end of the workshop production process (finish) – For public use, an additional finish application is required after installation. The pendulum value according to ÖNORM EN 13036-4 is 144. Natural coating material according to ÖNORM C 2380.

Intelligent Characteristics:

- Tongue and groove connection perfect for floating installation and full-surface bonding
- The plank appearance is emphasized thanks to bevel of the longitudinal and header joints
- Ideally suited to underfloor heating, as it can be completely adhered to the subfloor
- Wooden stairs WP MULTI - solutions for parquet and stairs from one source guarantee the best possible color uniformity

Concluding remark:

Measurements and technical specification of wood may be subject to insignificant technical material and production deviations. PEFC/FSC on request. Latest technical status of December 2017.

